This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

- 1. (Canceled)
- 2. (Canceled)
- 3. (Currently amended) The A lighting unit as defined in claim 2 wherein the lamp is a that provides adjustable beam spread, including at least one lighting cell comprising:

an elongated electric U-shaped tubular fluorescent lamp,
known as biax, having a curved end and a double contact end and
wherein: the;

an elongated reflector having a generally parabolic cross-sectional shape, symmetrically disposed about a central plane of symmetry that extends from a closed rear region of the reflector to a generally rectangular frontal light-exit aperture;

a first mounting assembly, made and arranged to support the double contact end of the lamp relative to the reflector, comprises comprising a first base bracket mounted fixedly relative to the reflector near a first end thereof and extending within the reflector, a socket-mount bracket adjustably attached to the first base bracket, and socket means for electrically connecting to the double contact end; and the

a second mounting assembly, made and arranged to support the curved end of the lamp relative to the reflector, comprises comprising a second base bracket mounted fixedly relative to the reflector near a second end thereof and extending within the reflector, a lamp-holder bracket, adjustably attached to the second base bracket, made and arranged to support the curved end of the lamp; the first and second mounting assemblies each being provided with a user handle made and arranged to enable a user to conveniently deploy any one of the three preset light source